
LEDVANCE SPOT KIT LED

LED spotlight luminaires



Areas of application

- Corridors
- Shop lighting
- Living rooms
- Foyers

Product benefits

- Direct replacement for conventional 50 W halogen luminaires
- Energy savings of up to 90 % compared to conventional recessed luminaires
- Single spot optics
- White die-cast zinc alloy ring
- Replaceable LED lamp
- Dimmable and non dimmable versions available
- Certificates: CE
- 3 years guarantee

Product features

- Luminaire efficacy: up to 84 lm/W
- Luminous flux: up to 420 lm
- Beam angle: 36°
- Spot can be swiveld 20° into all directions
- Lifetime (L70/B50): up to 25,000 h



Product family datasheet

Technical data

Product description	Electrical data				Photometrical data				Light technical data	Dimensions & weight
	Operating mode	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Light color (designation)	Color rendering index Ra	Beam angle	Diameter
KIT LED 5.50 W 3000 K DIM GU10	Mains voltage	5.50 W	220...240 V	50/60 Hz	3000 K	380 lm	Warm White	>80	36 °	83.0 mm
KIT LED 5.50 W 4000 K DIM GU10	Mains voltage	5.50 W	220...240 V	50/60 Hz	4000 K	420 lm	Cold White	>80	36 °	83.0 mm
KIT LED 4.70 W 3000 K GU10	Mains voltage	4.70 W	220...240 V	50/60 Hz	3000 K	380 lm	Warm White	>80	36 °	83.0 mm
KIT LED 4.70 W 4000 K GU10	Mains voltage	4.70 W	220...240 V	50/60 Hz	4000 K	420 lm	Cold White	>80	36 °	83.0 mm

Product description	Height	Mounting diameter	Colors & materials		Temperatures & operating conditions	Lifespan	Capabilities	
			Body material	Product color	Ambient temperature range	Lifespan	Adjustable	Dimmable
KIT LED 5.50 W 3000 K DIM GU10	113.0 mm	75.0 mm	Aluminum	White	-20...40 °C	25000 h	Yes	Yes
KIT LED 5.50 W 4000 K DIM GU10	113.0 mm	75.0 mm	Aluminum	White	-20...40 °C	25000 h	Yes	Yes
KIT LED 4.70 W 3000 K GU10	113.0 mm	75.0 mm	Aluminum	White	-20...40 °C	15000 h	Yes	Yes
KIT LED 4.70 W 4000 K GU10	113.0 mm	75.0 mm	Aluminum	White	-20...40 °C	15000 h	Yes	Yes

Product description	Type of connection	Holder designation	Certificates & standards		
			Protection class	Type of protection	Protection class IK (shock resistance)
KIT LED 5.50 W 3000 K DIM GU10	Terminal, 2-pin	GU10	II	IP20	IK02
KIT LED 5.50 W 4000 K DIM GU10	Terminal, 2-pin	GU10	II	IP20	IK02
KIT LED 4.70 W 3000 K GU10	Terminal, 2-pin	GU10	II	IP20	IK02
KIT LED 4.70 W 4000 K GU10	Terminal, 2-pin	GU10	II	IP20	IK02

Product family datasheet

KIT LED 5.50 W 3000 K DIM GU10, KIT
LED 5.50 W 4000 K DIM GU10, KIT
— LED 4.70 W 3000 K GU10, KIT LED
4.70 W 4000 K GU10

Application advice

For more detailed application information and graphics please see product datasheet.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075800908	KIT LED 5.50 W 3000 K DIM GU10	Shipping carton box 6	481 mm x 212 mm x 123 mm	12.54 dm ³	1529.00 g

Product family datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075800946	KIT LED 5.50 W 4000 K DIM GU10	Shipping carton box 6	481 mm x 212 mm x 123 mm	12.54 dm ³	1529.00 g
4058075800984	KIT LED 4.70 W 3000 K GU10	Shipping carton box 6	481 mm x 212 mm x 123 mm	12.54 dm ³	1529.00 g
4058075801004	KIT LED 4.70 W 4000 K GU10	Shipping carton box 6	481 mm x 212 mm x 123 mm	12.54 dm ³	1529.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For Guarantee see

▶ www.ledvance.com/guarantee

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.