

PRODUCT FAMILY DATASHEET ENDURA STYLE WALL

Slim LED luminaires with high light output and optional sensor



AREAS OF APPLICATION

- Outdoor
- Entrance lighting
- Building facades

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation

PRODUCT FEATURES


- Very bright and functional outdoor LED luminaires
- Type of protection: IP44
- Die-cast aluminum housing
- Available in two housing colors
- Available with and without motion sensor



TECHNICAL DATA

	Electrical data			Photometrical data		Dimensions & weight			Colors & materials		
Product description	Operating mode	Nominal wattage	Nominal voltage	Mains frequency	Color temper- ature	Luminous flux	Length	Width	Height	Product weight	Body material
ENDURA STYLE Wall 12 W DG	Mains voltage	11.50 W	220240 V	50/60 Hz	3000 K	740 lm	168.0 mm	100.0 mm	273.0 mm	1300.00 g	Aluminum
ENDURA STYLE Wall 12 W WT	Mains voltage	11.50 W	220240 V	50/60 Hz	3000 K	770 lm	168.0 mm	100.0 mm	273.0 mm	1300.00 g	Aluminum
ENDURA STYLE Wall Sensor 12 W DG	Mains voltage	12.20 W	220240 V	50/60 Hz	3000 K	740 lm	168.0 mm	100.0 mm	273.0 mm	1300.00 g	Aluminum
ENDURA STYLE Wall Sensor 12 W WT	Mains voltage	12.20 W	220240 V	50/60 Hz	3000 K	770 lm	168.0 mm	100.0 mm	273.0 mm	1300.00 g	Aluminum

			Temperatures & operating conditions	Lifespan	Capabilities		Certificates & standards	
Product description	Product color	Cover material	Ambient temperature range	Lifespan	Dimmable	Type of connection	Protection class	Type of protection
ENDURA STYLE Wall 12 W DG	Dark gray	Glass	-2040 °C	30000 h	No	Terminal	ı	IP44
ENDURA STYLE Wall 12 W WT	White	Glass	-2040 °C	30000 h	No	Terminal	I	IP44
ENDURA STYLE Wall Sensor 12 W DG	Dark gray	Glass	-2040 °C	30000 h	No	Terminal	I	IP44
ENDURA STYLE Wall Sensor 12 W WT	White	Glass	-2040 °C	30000 h	No	Terminal	I	IP44



ENDURA STYLE Wall 12 W DG, ENDURA STYLE Wall 12 W WT, ENDURA STYLE Wall Sensor 12 W DG, ENDURA STYLE Wall Sensor 12 W WT

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075033191	ENDURA STYLE Wall 12 W DG	Shipping carton box 4	425 mm x 285 mm x 315 mm	38.15 dm³	6668.00 g

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075033214	ENDURA STYLE Wall 12 W WT	Shipping carton box 4	425 mm x 285 mm x 315 mm	38.15 dm³	6684.00 g
4058075033238	ENDURA STYLE Wall Sensor 12 W DG	Shipping carton box 4	425 mm x 285 mm x 315 mm	38.15 dm³	6879.00 g
4058075033252	ENDURA STYLE Wall Sensor 12 W WT	Shipping carton box 4	425 mm x 285 mm x 315 mm	38.15 dm³	6890.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.