

---

## LEDVANCE PANEL LED 1200x300

### LED panel luminaires



---

#### Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Corridors
- Offices
- Conference rooms
- Reception areas
- Foyers

---

#### Product benefits

- High luminous efficacy
- Energy savings of up to 50 % compared to conventional luminaires
- Easy and quick installation
- Very homogenous light
- 5 years guarantee
- Very slim aluminum housing (only 10.5 mm) and matt white frame
- Certificates: CE

---

#### Product features

- Type of protection: IP20
- Aluminum housing, polystyrene diffuser
- Ambient temperature in operation: -10...+45 °C
- Lifetime (L70/B50): up to 50,000 h (at 25 °C)



## Product family datasheet

### Technical data

Product description	Electrical data				Photometrical data				Light technical data	Dimensions & weight
	Operating mode	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Light color (designation)	Color rendering index Ra	Beam angle	Length
PANEL LED 1200 33 W 3000 K UGR < 19	Electronic control gear (EVG)	33.00 W	220...240 V	50/60 Hz	3000 K	3100 lm	Warm White	>80	90.00 °	1195 mm
PANEL LED 1200 33 W 4000 K UGR < 19	Electronic control gear (EVG)	33.00 W	220...240 V	50/60 Hz	4000 K	3300 lm	Cool White	>80	90.00 °	1195 mm
PANEL LED 1200 40 W 4000 K	Electronic control gear (EVG)	40.00 W	220...240 V	50/60 Hz	4000 K	4000 lm	Cool White	>80	120 °	1195 mm
PANEL LED 1200 40 W 3000 K	Electronic control gear (EVG)	40.00 W	220...240 V	50/60 Hz	3000 K	4000 lm	Warm White	>80	120 °	1195 mm

Product description			Colors & materials		Temperatures & operating conditions	Capabilities	Certificates & standards	
	Width	Height	Body material	Product color	Ambient temperature range	Dimmable	Protection class	Type of protection
PANEL LED 1200 33 W 3000 K UGR < 19	295.0 mm	10.5 mm	Aluminum	White	-10...45 °C	No	II	IP20
PANEL LED 1200 33 W 4000 K UGR < 19	295.0 mm	10.5 mm	Aluminum	White	-10...45 °C	No	II	IP20
PANEL LED 1200 40 W 4000 K	295.0 mm	10.5 mm	Aluminum	White	-10...45 °C	No	II	IP20
PANEL LED 1200 40 W 3000 K	295.0 mm	10.5 mm	Aluminum	White	-10...45 °C	No	II	IP20

### Application advice

For more detailed application information and graphics please see product datasheet.

## Product family datasheet

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075807266	PANEL LED 1200 33 W 3000 K UGR < 19	Shipping carton box 4	1295 mm x 180 mm x 355 mm	82.75 dm <sup>3</sup>	16090.00 g
4058075807280	PANEL LED 1200 33 W 4000 K UGR < 19	Shipping carton box 4	1295 mm x 180 mm x 355 mm	82.75 dm <sup>3</sup>	15960.00 g
4058075807303	PANEL LED 1200 40 W 4000 K	Shipping carton box 4	1295 mm x 180 mm x 355 mm	82.75 dm <sup>3</sup>	15200.00 g
4058075807327	PANEL LED 1200 40 W 3000 K	Shipping carton box 4	1295 mm x 180 mm x 355 mm	82.75 dm <sup>3</sup>	15320.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### References / Links

For Guarantee see

▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.