
LEDVANCE SURFACE CIRCULAR LED

LED wall and ceiling luminaires



Areas of application

- Corridors
- Stairways
- Bathrooms
- Foyers

Product benefits

- High luminous efficacy
- Energy savings of up to 55 % compared to conventional luminaires
- Easy and quick installation
- Very homogenous light
- LED protected for safe installation
- 3 years guarantee

Product features

- Beam angle: 120°
- Type of protection: IP44
- Impact resistance: IK03
- Metal housing, PMMA cover
- Ambient temperature in operation: -20...+40 °C
- Lifetime (L70/B50): up to 30,000 h (at 25 °C)
- Certificates: CE, CB, TUEV SUED
- Versions with movement and daylight sensor available (microwave sensor)



Product family datasheet


Technical data

Product description	Electrical data				Photometrical data				Light technical data	Dimensions & weight
	Operating mode	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Light color (designation)	Color rendering index Ra	Beam angle	Diameter
WALL AND CEILING LED 18 W 3000 K IP44	Electronic control gear (EVG)	18.00 W	220...240 V	50/60 Hz	3000 K	1440 lm	Warm White	>80	120 °	350.0 mm
WALL AND CEILING LED 18 W 4000 K IP44	Electronic control gear (EVG)	18.00 W	220...240 V	50/60 Hz	4000 K	1440 lm	Cool White	>80	120 °	350.0 mm
WALL AND CEILING LED 24 W 3000 K IP44	Electronic control gear (EVG)	24.00 W	220...240 V	50/60 Hz	3000 K	1920 lm	Warm White	>80	120 °	400.0 mm
WALL AND CEILING LED 24 W 3000 K IP44 SENSOR	Electronic control gear (EVG)	24.00 W	220...240 V	50/60 Hz	3000 K	1920 lm	Warm White	>80	120 °	400.0 mm
WALL AND CEILING LED 24 W 4000 K IP44	Electronic control gear (EVG)	24.00 W	220...240 V	50/60 Hz	4000 K	1920 lm	Cool White	>80	120 °	400.0 mm
WALL AND CEILING LED 24 W 4000 K IP44 SENSOR	Electronic control gear (EVG)	24.00 W	220...240 V	50/60 Hz	4000 K	1920 lm	Cool White	>80	120 °	400.0 mm


Product description	Height	Colors & materials		Temperatures & operating conditions	Lifespan	Capabilities		Certificates & standards	
		Body material	Product color	Ambient temperature range	Lifespan	Dimmable	Type of connection	Protection class	Type of protection
WALL AND CEILING LED 18 W 3000 K IP44	115.0 mm	Steel	White	-20...40 °C	30000 h	No	Terminal, 3-pin	I	IP44
WALL AND CEILING LED 18 W 4000 K IP44	115.0 mm	Steel	White	-20...40 °C	30000 h	No	Terminal, 3-pin	I	IP44
WALL AND CEILING LED 24 W 3000 K IP44	120.0 mm	Steel	White	-20...40 °C	30000 h	No	Terminal, 3-pin	I	IP44

Product family datasheet


Product description	Height	Colors & materials		Temperatures & operating conditions	Lifespan	Capabilities		Certificates & standards	
		Body material	Product color	Ambient temperature range	Lifespan	Dimmable	Type of connection	Protection class	Type of protection
WALL AND CEILING LED 24 W 3000 K IP44 SENSOR	120.0 mm	Steel	White	-20...40 °C	30000 h	No	Terminal, 3-pin	I	IP44
WALL AND CEILING LED 24 W 4000 K IP44	120.0 mm	Steel	White	-20...40 °C	30000 h	No	Terminal, 3-pin	I	IP44
WALL AND CEILING LED 24 W 4000 K IP44 SENSOR	120.0 mm	Steel	White	-20...40 °C	30000 h	No	Terminal, 3-pin	I	IP44




WALL AND CEILING LED 18 W 3000 K IP44, WALL AND CEILING LED 18 W 4000 K IP44



WALL AND CEILING LED 24 W 3000 K IP44, WALL AND CEILING LED 24 W 3000 K IP44 SENSOR, WALL AND CEILING LED 24 W 4000 K IP44, WALL




WALL AND CEILING LED 18 W 4000 K IP44



WALL AND CEILING LED 24 W 4000 K IP44

Product family datasheet

AND CEILING LED 24 W 4000 K IP44
SENSOR



WALL AND CEILING LED 24 W 4000 K
IP44 SENSOR

Application advice

For more detailed application information and graphics please see product datasheet.

Logistical Data

Product family datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075000742	WALL AND CEILING LED 18 W 3000 K IP44	Shipping carton box 5	625 mm x 410 mm x 410 mm	105.06 dm ³	5200.00 g
4058075000766	WALL AND CEILING LED 18 W 4000 K IP44	Shipping carton box 5	625 mm x 410 mm x 410 mm	105.06 dm ³	5862.00 g
4058075000780	WALL AND CEILING LED 24 W 3000 K IP44	Shipping carton box 5	700 mm x 450 mm x 460 mm	144.90 dm ³	6756.00 g
4058075000827	WALL AND CEILING LED 24 W 3000 K IP44 SENSOR	Shipping carton box 5	700 mm x 450 mm x 460 mm	144.90 dm ³	6976.00 g
4058075000803	WALL AND CEILING LED 24 W 4000 K IP44	Shipping carton box 5	700 mm x 450 mm x 460 mm	144.90 dm ³	6927.00 g
4058075000841	WALL AND CEILING LED 24 W 4000 K IP44 SENSOR	Shipping carton box 5	700 mm x 450 mm x 460 mm	144.90 dm ³	6927.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For Guarantee see

▶ www.ledvance.com/guarantee

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.